

Hikvision DS-2CE70DF0T-LPFS/S 2MP Smart Hybrid Light Dome CC Camera

Sale Price: 2500.0

PRODUCT ID: 0011712

General

Dimensions	Ø85.02 mm × 81.25 mm (Ø3.35″ × 3.2″)
Weight	Approx. 155 g (0.34 lb.)
Pan/Tilt/Rotation	Pan: 0° to 360°,Tilt: 0° to 75°,Rotate: 0° to 360°
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F). Humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 2.9 W

Camera

Image Sensor	2MP CMOS
Electronic Shutter Speed	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Minimum Illumination	0.001 Lux @ (F1.0, AGC ON), 0 Lux with white light
IR Distance	Supplement Light Type: Smart, IR, White Light Supplement Light Range: IR: Up to 20 m,White Light: Up to 20 m

Lens

Lens Type	2.8 mm, 3.6 mm fixed focal lens
Mount Type	M12
Focal Length	2.8 mm, horizontal FOV: 105°, vertical FOV: 56°, diagonal FOV: 126° 3.6 mm, horizontal FOV: 84°, vertical FOV: 46°, diagonal FOV: 98°

Video

Resolution	1920 × 1080
Frame Rate	TVI: 2K @20fps, 1080P @25fps/30fps AHD: 1080P @25fps/30fps CVI: 1080P @25fps/30fps CVBS: PAL/NTSC
Day/Night	ICR
BLC Mode	Yes
BLC Mode	Yes
Noise Reduction	3D DNR/2D DNR

Interface

Video Interface	Switchable TVI/AHD/CVI/CVBS

Special Features

Features	Wide Dynamic Range (WDR): Digital WDR Image Enhancement: DWDR/BLC/HLC/Global White Balance: Auto/Manual AGC: Yes

Warranty

Warranty	01 year warranty