

Dahua 2MP Smart Dual Light HDCVI Bullet 30 MTR IR Distance, Lens 3.6mm (Plastic)#DH-HAC-B1A21P-U-IL



Sale Price: 1700.0

PRODUCT ID: 01839

General

| | |
|----------------------|---|
| Casing | Metal front cover + plastic rear barrel + metal bracket |
| Dimensions | 146.1 mm × 70.0 mm × 69.8 mm (5.75" × 2.76" × 2.75") |
| Weight | 0.23 kg (0.51 lb) |
| Pan/Tilt/Rotation | Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360° |
| Operating Conditions | –40 °C to +60 °C (–40 °F to +140 °F) |
| Storage Conditions | –40 °C to +60 °C (–40 °F to +140 °F) |
| Power Supply | 12 VDC ± 30% |
| Power Consumption | Max 3.3 W (12 VDC, WLED on) |

Camera

| | |
|--------------------------|---|
| Image Sensor | 2 MP CMOS |
| Effective Pixels | 1920 (H) × 1080 (V) |
| Scanning System | Progressive |
| Electronic Shutter Speed | PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s |
| Minimum Illumination | 0.02 lux@F2.0 (Color, 30 IRE); 0.002 lux@F2.0 (B/W, 30 IRE); 0 lux (Illuminator on) |
| S/N Ratio | >65 dB |
| IR Distance | IR: 30 m (98.43 ft); Warm light: 20 m (65.62 ft) |
| IR On/Off Control | Auto / Manual |

General

| | |
|---------|-----------------------------|
| IR LEDs | 2 (Warm light);2 (IR light) |
|---------|-----------------------------|

Lens

| | |
|----------------------|--|
| Lens Type | Fixed-focal |
| Mount Type | M12 |
| Focal Length | 2.8 mm; 3.6 mm; 6 mm |
| Max Aperture | F2.0 |
| Angle of View | 2.8 mm: H: 100°; V: 54°; D: 117° 3.6 mm: H: 80°; V: 43°; D: 94° 6 mm: H: 43°; V: 24°; D: 50° |
| Close Focus Distance | 2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.8 m (2.62 ft) 6 mm: 2.4 m (7.87 ft) |

Video

| | |
|-----------------|---|
| Resolution | 1080p (1920 × 1080); 960H (960 × 576/960 × 480) |
| Frame Rate | CVI: PAL: 1080p@25 fps NTSC: 1080p@30 fps AHD: PAL: 1080p@25 fps NTSC: 1080p@30 fps TVI: PAL: 1080p@25 fps NTSC: 1080p@30 fps CVBS: PAL: 960H NTSC: 960H |
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port |
| Day/Night | Auto(ICR)/Color/B/W |
| BLC Mode | BLC; HLC; DWDR |
| Gain Control | Auto/Manual |
| Noise Reduction | 2D NR |

Interface

| | |
|-----------------|--|
| Audio Interface | Video output choices of CVI/TVI/AHD/CVBS by one BNC port |
| Video Interface | One channel built-in mic |

Special Features

General

Features

Smart Dual Light.
30 m illumination distance.
Super Adapt.
Built-in MIC.
IP67

Warranty

Warranty

1 Year