

Dahua 2MP Smart Dual Light HDCVI Dome 25 MTR IR Distance, Lens 2.8 MM (Plastic)#DH-HAC-T1A21P-U-IL



Sale Price: 1700.0

PRODUCT ID: 01844

General

Casing	Plastic
Dimensions	Φ85.0 mm × 77.1 mm (Φ3.35" × 3.04")
Weight	0.12 kg (0.26 lb)
Pan/Tilt/Rotation	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°
Operating Conditions	Temperature: -40 °C to +60 °C (-40 °F to +140 °F) Humidity: <95% (RH), non-condensing
Storage Conditions	Temperature: -40 °C to +60 °C (-40 °F to +140 °F) Humidity: <95% (RH), non-condensing
Power Supply	12 VDC ± 30%
Power Consumption	Max 2.1 W (12 VDC, LED on)

Camera

Image Sensor	2 MP CMOS
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s
Minimum Illumination	0.02 lux@F2.0 (Color, 30 IRE); 0.002 lux@F2.0 (B/W, 30 IRE); 0 lux (Illuminator on)
S/N Ratio	>65 dB
IR Distance	IR: 25 m (82.02 ft); Warm light: 20 m (65.62 ft)

General

IR LEDs	2 (Warm light);2 (IR light)
---------	-----------------------------

Lens

Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8 mm;3.6 mm
Max Aperture	F2.0
Angle of View	2.8 mm: H: 100°; V: 54°; D: 117° 3.6 mm: H: 80°; V: 43°; D: 94°
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.8 m (2.62 ft)

Video

Resolution	1080p (1920 × 1080); 960H (960 × 576/960 × 480)
Frame Rate	CVI: PAL: 1080p@25 fps NTSC: 1080p@30 fps AHD: PAL: 1080p@25 fps NTSC: 1080p@30 fps TVI: PAL: 1080p@25 fps NTSC: 1080p@30 fps CVBS: PAL: 960H NTSC: 960H
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC; HLC; DWDR
Gain Control	Auto;Manual
Noise Reduction	2D NR
Interface	
Video Interface	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Warranty	
Warranty	1 year