



Dahua 5MP Smart Dual Light HDCVI Dome 20 MTR IR Distance, Lens 2.8 MM With Built In Mic (Plastic)#DH-HAC-HDW1500CLQP-IL-A

Sale Price: 2500.0

PRODUCT ID: 01860

General

Casing	Plastic
Dimensions	φ97.1 mm × 93.8 mm (φ3.82" × 3.69")
Weight	Net Weight 0.19 kg (0.42 lb) Gross Weight 0.3 kg (0.66 lb)
Pan/Tilt/Rotation	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°
Operating Conditions	Operating Temperature –40 °C to +55 °C (–40 °F to +131 °F) Operating Humidity <95% (RH), non-condensing
Storage Conditions	Storage Temperature –40 °C to +55 °C (–40 °F to +131 °F) Storage Humidity <95% (RH), non-condensing
Power Supply	12 VDC ± 30%
Power Consumption	Max 4.5 W (12 VDC, WLED on)

Camera

Image Sensor	5 MP CMOS
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s
Minimum Illumination	0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>65 dB
IR Distance	20 m (65.62 ft) Warm Light: 20 m (65.62 ft)
IR On/Off Control	Auto/Manual

General

Lens

Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8 mm; 3.6 mm
Max Aperture	F1.6
Angle of View	2.8 mm: H: 106°; V: 56°; D: 125° 3.6 mm: H: 92°; V: 48°; D: 109°
Focus Control	Fixed
Close Focus Distance	2.8 mm: 0.8 m (2.62 ft) 3.6 mm: 1.3 m (4.27 ft)

Video

Resolution	2880 (H) × 1620 (V)
Frame Rate	CVI: PAL: 5M@25 fps; 4M@25 fps; 1080p@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080p@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto(ICR)/Color/B/W
Gain Control	Auto/Manual
Noise Reduction	2D NR

Warranty

Warranty	1 Year
----------	--------