

Dahua 32 Channel Wizensense XVR (2 Sata UP to 16TB) 4K HDMI, H265/H.265+, UP To 5MP Camera Supports #DH-XVR5232AN-I3

Sale Price: 44000.0



PRODUCT ID: 01846

System

Main Processor	Industrial-grade processor
Operating System	Embedded LINUX

Audio and Video

IP Camera Input	Up to 32 channels of IPC access 32 channels (analog channels are converted to IP channels) incoming bandwidth: 128 Mbps, recording bandwidth: 128 Mbps and outgoing bandwidth: 128 Mbps
Two-Way Talk	Yes (share the same audio input with the first channel)

Display

Interface	1 HDMI, 1 VGA, 1 TV
Resolution	VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720
Multi-Screen Display	1/4/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

Recording

Compression	Video Compression: AI Coding; Smart H.265+; H.265; Smart H.264+; H.264 Audio Compression: G.711a; G.711u; PCM
Record Rate	Main stream: 5M-N@(1fps-10fps); 4M-N,1080p@(1fps-15fps); 1080N, 720p, 960H, D1,CIF@(1fps-25/30fps) Sub stream: D1, CIF@(1fps-15fps)
Bit Rate	32 kbps-6144 kbps
Record Mode	General, motion detection; intelligent; alarm; POS

Playback And Backup

System

Playback Function Instant playback, general playback, event playback, tag playback, smart playback (face and motion detection)

Backup Mode USB device and network

Network

Ethernet Port 1 (10/100/1000 Mbps Ethernet port, RJ-45)

Storage

Internal HDD 2 SATA ports, up to 16TB capacity for each disk. The maximum HDD capacity varies with environment temperature.

Auxiliary Interface

USB 2 (1 front USB 2.0 port, 1 rear USB 3.0 port)

RS485 1 port, for PTZ control

Power

Power Supply DC 12V, 5A

Power Consumption <16 W (without HDD)

Component Environment

Operational Conditions -10 °C to +55 °C (14 °F to +131 °F)

Construction

Dimensions 375.0 mm × 289.4 mm × 53.0 mm (14.76" × 11.40" × 2.09") (W × D × H)

Net Weight 1.90 kg (4.20 lb)

Gross Weight 3.20 kg (7.00 lb)

Warranty

Manufacturing Warranty 1 year