

## Uniview XVR301-16F 16 Channel 1080P XVR

Sale Price: 8500.0



PRODUCT ID: 09718

Brand	Uniview
Model	XVR301-16F
Type	16 Channel 1 SATA XVR
SATA	1 SATA interface
Capacity	Up to 6TB for each HDD
Analog Video Input	16-ch, BNC
IP Video Input	2-ch (only IP up to 18ch), each channel up to 8MP
Supported Analog Camera Types	Support AHD input: 1080P@30fps 720P@30fps Support TVI input: 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input
Audio Compression	G.711U
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Live view display	HDMI/VGA: 1/4/6/8/9/16/25
Synchronous Playback	HD:16-ch SD:16-ch
FTP/Schedule/Event Snapshot	Schedule snapshot is not supported 16-ch snapshot, up to 704*576 resolution
Recording Resolution	1080P Lite/720P/D1
Recording Frame Rate	Main stream: 1080P Lite@12fps   720P@15fps Sub stream: D1@12fps   D1@15fps
Audio Sample Rate	8KHz, 16 bit per channel

Audio Bit Rate	64Kbps per channel
Capability	Analog:16x 1080P Lite@12, 16x 720P@15 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30, 8 x 720P@30,16 x D1@30
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Incoming Bandwidth	24Mbps (Up to 56Mbps after all-analog channel conversion)
Outgoing Bandwidth	64Mbps
Web Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows
Remote Users	128
General Alarm	Motion detection
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
VCA Detection	Ultra Motion Detection(UMD) for analog:8-ch
VCA Search	Behavior Search
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0
Power	12V DC Power Consumption: ≤ 10 W( without HDD )
Working Environment	-10°C ~ + 55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)
Certification	UL/CE/FCC /RoHS /WEEE
Warranty Details	1-Year Brand Warranty