

GIGABYTE H410M H V2 10th Gen Micro ATX Motherboard

Sale Price: 9800.0



PRODUCT ID: 0001207

Basic

Information

Supported CPU	Support for 10th Generation Intel Core i9 processors/ Intel Core i7 processors/ Intel Core i5 processors/Intel Core i3 processors/ Intel Pentium processors/ Intel Celeron processors in the LGA1200 package
Chipset	Intel H470 Express Chipset
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor: 22.6cm x 18.5cm
Audio	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel

Expansion

Slots

PCI	1 x PCI Express x16 slot, running at x16 2 x PCI Express x1 slots (The PCI Express slots conform to PCI Express 3.0 standard.) Supports up to ASPM L1.2 power management protocols.
-----	--

Memory

Type	DDR4
Slots	2 x DIMM
Supported Memory	Intel Core i9/i7 processors: Support for DDR4 2933/2666/2400/2133 MHz memory modules Intel Core i5/i3/Pentium/Celeron processors: Support for DDR4 2666/2400/2133 MHz memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Maximum Memory	64GB (32 GB single DIMM capacity)

Graphics

Information

Graphics	Integrated Graphics Processor-Intel HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI ports, supporting a maximum resolution of 4096x2160@30 Hz * Support for HDMI 1.4 version and HDCP 2.3.
----------	--

Max Shared Memory	512MB
----------------------	-------

Connector & Ports

HDMI	1 x HDMI port
D-Sub (s)	1 x D-Sub port
USB (s)	Chipset: 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) 6 x USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header)
LAN Port (s)	Intel GbE LAN chip (1 Gbit/100 Mbit)
Supported Storage	1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe x4/x2 SSD support) 4 x SATA 6Gb/s connectors Intel Optane Memory Ready M.2 connectors support up to ASPM L1.2 PCIe power management protocols.
RAID	Support for RAID 0, RAID 1, RAID 5, and RAID 10
Internal I/O Ports	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 1 x system fan header 1 x RGB LED strip header 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x serial port header 1 x Clear CMOS jumper
TPM (Trusted Platform Module)	1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

Others

Information

Special Features

Support for APP Center

* Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.

@BIOS

Ambient LED

EasyTune

Fast Boot

Game Boost

ON/OFF Charge

Smart Backup

System Information Viewer

Support for Q-Flash

Support for Xpress Install

Bundled
Software

Norton Internet Security (OEM version)
cFosSpeed

Warranty Information

Manufacturing
Warranty

03 Years