



Hikvision 4MP Smart Duel Light Dome Network Camera 30 MTR Distance, Lens 2.8 MM #DS-2CD1343G2-LIU

Sale Price: 5000.0

PRODUCT ID: 0001564

General

Dimensions	Ø110 mm × 89.2 mm (Ø4.3" × 3.5")
Weight	Approx. 340 g (0.7 lb.)
Pan/Tilt/Rotation	Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°
Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, 0.4 A, max. 5 W, Ø5.5 mm coaxial power plug, reverse polarity protection, PoE: IEEE 802.3af, Class 3, max. 6.5 W

Camera

Image Sensor	4MP 1/3" Progressive Scan CMOS
Effective Pixels	2560 × 1440
Minimum Illumination	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
IR Distance	30 m

Lens

Lens Type	2.8 mm fixed focal lens
Mount Type	M12
Focal Length	2.8 mm, horizontal FOV 98°, vertical FOV 54°, diagonal FOV 114°
Max Aperture	F1.6

Video

Frame Rate	Main Stream 50 Hz: 20 fps (2560 × 1440) 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 20 fps (2560 × 1440) 24 fps (1920 × 1080, 1280 × 720) Sub-Stream 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 24 fps (1280 × 720, 640 × 480, 640 × 360)
Day/Night	Color

Interface

Audio Interface

Audio Type: Mono sound

Environment Noise Filtering: Yes

Audio Sampling Rate: 8 kHz/16 kHz

Audio Compression: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC

Audio Bit Rate: 64 Kbps (G.711 ulaw)/64 Kbps (G.711 alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)

Warranty

Warranty

01 year warranty