

Hikvision 4MP Bullet Network Camera 60 MTR Distance, Lens 4.00 MM With Built In Mic #DS-2CD2T43G2-2I



Sale Price: 8500.0

PRODUCT ID: 03500

— Camera Feature

Image Sensor	1/3" Progressive Scan CMOS Video Compression: H.265+/H.265/H.264+/H.264/MJPEG Video bit rate: 256Kbps~16Mbps Triple Streams: Yes
Effective Pixels	Image- 4 MP Max. Image Resolution: 2688 × 1520 Frame Rate: 50Hz:25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) Sub Stream: 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240) Third Stream: 50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240) Image Enhancement: BLC/3D DNR/ROI/HLC Image Settings: Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser Target Cropping: No ROI: 1 fixed region for main stream and sub-stream Day/Night Switch: Day/Night/Auto/Schedule
IR Distance	Up to 60 m IR range

Camera Feature

Others	Behavior Analysis: Line crossing detection, intrusion detection Line Crossing Detection: Cross a pre-defined virtual line Intrusion Detection: Enter and loiter in a pre-defined virtual region Detection/Recognition: Face Detection
--------	--

Lens

Focal Length	2.8 mm @ F1.6: horizontal FOV: 103°, vertical FOV: 58°, diagonal FOV: 123° 4 mm @F1.6: horizontal FOV: 83°, vertical FOV: 45°, diagonal FOV: 99° 6 mm @F1.6: horizontal FOV: 51°, vertical FOV: 29°, diagonal FOV: 58° 8 mm @F1.6: horizontal FOV: 39°, vertical FOV: 22°, diagonal FOV: 45°
Angle of View	Adjustment Range: Pan: 0° to 360°, tilt: 0° to 100°, rotate: 0° to 360°
Others	Day& Night: IR cut filter with auto switch Wide Dynamic Range: 120 dB Digital noise reduction: 3D DNR Focus: Fixed

Physical Specification

Dimension	Camera: Φ 105 × 299.7 mm (Φ 4.1" × 11.8") Package: 386 × 156 × 155 mm (15.2" × 6.14" × 6.1")
Weight	Camera: Approx. 1180 g (2.6 lb.) With Package: Approx. 1700 g (3.7 lb.)
Power	Power Supply: 12 VDC ± 25%, PoE (802.3af Class3) Power Consumption: I8:12 VDC, 0.95A, max. 11.5W PoE (802.3af, 37V to 57V), 0.35A to 0.1A, max. 12.5W
Interface	Communication Interface: 1 RJ45 10M / 100M Ethernet interface On-board storage: Built-in Micro SD/SDHC/SDXC slot, up to 128 GB Reset Button: Yes

Camera Feature

Others

Lens Mount:

M12

Adjustment Range:

Pan: 0° to 360°, tilt: 0° to 100°, rotate: 0° to 360°

Day& Night:

IR cut filter with auto switch

Wide Dynamic Range:

120 dB

Digital noise reduction:

3D DNR

Focus:

Fixed