



Hikvision 4MP PT Network Camera 30 MTR Distance, Lens 4.00 MM With Built In Mic #DS-2DE2C400MWG-E

Sale Price: 7000.0

PRODUCT ID: 03503

— Camera Feature

Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	4MP (2560 × 1440)
IR Distance	White light distance: up to 30 m, IR distance: up to 30 m
Others	Min. Illumination: Color: 0.01 Lux @ (F2.0, AGC ON), B/W: 0.005 Lux @ (F2.0, AGC ON), 0 Lux with light

Lens

Type	4 mm/ 2.8 mm
Aperture	F1.6
Angle of View	4 mm, horizontal FOV 70°, vertical FOV 35°, diagonal FOV 85°
Others	Movement Range (Pan): 0° to 345° Movement Range (Tilt): 0° to 80° Pan Speed: Up to 25°/s Tilt Speed: Up to 20°/s

Physical

Specification

Dimension	163.9 mm × 185.8 mm × 131.9 mm (6.45" × 7.31" × 5.19")
Weight	600 g (1.32 lb.)
Power	12 VDC ± 25%, 0.75 A, max. 9 W, Ø5.5 mm coaxial power plug, reverse polarity protection, PoE: IEEE 802.3af, 36 V to 57 V, 0.2 A to 0.3 A, max. 10.5 W
Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port 1 built-in microphone 1 built-in speaker Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

Camera Feature

Others

IP66 Water and dust resistant

Hik-Connect cloud service and APP for remote management and views of devices

General Function: Mirror, password protection, watermark

Basic Event: Motion detection (support alarm triggering by specified target type (human)), video tampering alarm, exception

Linkage: Upload to FTP/memory card, notify surveillance center, send email, trigger capture, audible warning, auto-tracking lite

Warranty

Warranty

1 Years