

TP-Link Archer C50 AC1200 Mbps Ethernet Dual-Band Wi-Fi Router

Sale Price: 2600.0

PRODUCT ID: 0005550

Key Features

Data Rate	2.4GHz: Up to 300Mbps 5GHz: Up to 867Mbps
Antenna	4 External Antennas
Button	Reset Button WPS/Wi-Fi On/Off Button Power On/Off Button
Frequency	2.4GHz and 5GHz
Wireless	IEEE 802.11n/g/b 2.4GHz IEEE 802.11ac/n/a 5GHz
Interface	4 10/100Mbps LAN Ports 1 10/100Mbps WAN Port
Network Standard	5GHz: 11a 54M: -73dBm 11ac VHT20 MCS8: -68dBm 11ac VHT40 MCS9: -64dBm 11ac VHT80 MCS9: -60dBm 2.4GHz: 11g 54M: -76dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71d
Encryption	64/128-bit WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption
Ports	1× 10/100 Mbps WAN Port 4× 10/100 Mbps LAN Ports

Others	1200 sq ft to 1500 sq ft Maximum Area Open Space Coverage Operating Temperature: 0℃~40 ℃ (32 ℉~104℉) Storage Temperature: -40℃~70 ℃ (-40 ℉~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing CE, FCC, RoHS 2.4GHz guest network × 1 5GHz guest network × 1 Supports IPv4 and IPv6 DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding Parental Control, Local Management Control, Host List, Access Schedule, Rule Management PPTP, L2TP, IPSec DynDns, Comex, NO-IP Virtual Server, Port Triggering, UPnP, DMZ Server, Client, DHCP Client List, Address Reservation Access Control Local Management Remote Management Dynamic IP/Static IP/PPPoE/ BigPond/ /L2TP(Dual Access) /PPTP(Dual Access)
Operating System Support	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, Windows 8/8.1/10 MAC OS, NetWare, UNIX or Linux

Power Source

Power Mode	CE: <20dBm(2.4GHz) <23dBm(5GHz) FCC: <30dBm External Power Supply-9VDC / 0.85A

Physical Dimension

Dimension	9.1 x 5.7 x 1.5 in. (229.87 x 144.19 x 36.85 mm)

Manufacturer warranty

Warranty	01 year warranty