



Dahua DH-IPC-H5AS 5MP Indoor Fixed-focal Smart Dual Light Wi-Fi Pan & Tilt Network Camera

Sale Price: 3200.0

PRODUCT ID: 0014015

Camera	
Image Sensor	1/3.2" CMOS
Max. Resolution	2880 (H) × 1620 (V)
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Illumination Distance	Up to 20 m (65.62 ft) (IR) Up to 10 m (32.81 ft) (Warm light)
Illuminator On/Off Control	Auto
Illuminator Number	1 (Multi-core (IR + warm) light)
Angle Adjustment	Pan: 0° to 355°; Tilt: -5° to 80°
Lens	
Max. Aperture	F2.0
Field of View	H: 95°; V: 53°; D: 110°
Intelligence	

Pet Detection	Yes
Video	
Video Compression	H.265; H.264
Video Frame Rate	Main stream: 2880 × 1620@15 fps, max up to 25 fps; Sub stream: 640 × 360@15 fps, max up to 25 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Resolution	5M (2880 × 1620); nHD (640 × 360)
Video Bit Rate	H.265: 32 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°
Audio	
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n/a/ac/ax 2.4 G & 5 G, EIRP≤20 dBm@2400–2483.5 MHz (CE), EIRP≤23 dBm@5150–5250 MHz (CE), EIRP≤20 dBm@5250–5350 MHz (CE), EIRP≤27 dBm@5470–5725 MHz (CE), EIRP≤14 dBm@5725–5875 MHz (CE)

Management Software	DMSS
Mobile Client	iOS;Android
Certification	
Certifications	CE
Power	
Power Supply	5 VDC (±5%)
Power Consumption	Basic: 1.565 W (5 VDC); Max.: 3.72 W (5 VDC) (WDR + intelligence + warning sound + warning light)
Environment	
Operating Temperature	-10 °C to +45 °C (+14 °F to +113 °F)
Operating Humidity	≤95% (RH), non-condensing
Structure	
Casing Material	Plastic
Product Dimensions	Φ77.8 mm × 112.1 mm (Φ3.06" × 4.41")
Net Weight	0.2 kg (0.44 lb)