



Apollo 2000VA Offline UPS

Sale Price: 16700.0

PRODUCT ID: 0015,063

Main Feature	
Capacity	2000VA
Load Capacity	900W
Input Voltage	220VAC $\pm$ 20~35% (Customizable)
Output Voltage	220VAC $\pm$ 3~8%
Frequency (Battery Mode)	50 Hz or 60Hz $\pm$ 1Hz
Noise Level	EMI/RFI full time suppression
Battery	Types: Lead-Acid maintenance-free DC Bus: 12V/7.2A Number: 4 PCS Recharge Time: Typically 8 hours to 90% Charged Backup Time: 15~30 Minutes Depending on load connected (Long Backup Optional)
Alarm	Beeping Alarm
Indications	AC Mode: Green lighting Battery Mode: Red lighting Over Load: Yellow lighting
Input Features	
Frequency	50Hz or 60Hz
Voltage Range	220VAC $\pm$ 20~35% (Customizable)
Output Features	
Backup Time	15~30 Minutes Depending on load connected (Long Backup Optional)
Voltage Range	220VAC $\pm$ 3~8%
Transfer Time	2ms
Physical Specification	
Dimension	165x228x483mm
Manufacture Warranty	

- UPS burning due to thunder, abnormal overload, insect entrance and others.
- If ambient temperature should not be maintained at 20 to 26 degrees Celsius with proper dehumidification. (24/7)
- If the product is placed in a dusty and damp place.
- In the absence of Generator connectivity Without proper battery charge, the warranty will be void.
- Battery swelling and overcharging due to the wrong system voltage setting of the UPS.