

Tipsoi Fastface Go Lite Time Attendance & Access Control Terminal

Sale Price: 40500.0

PRODUCT ID: 0015115

Face Capacity	10,000 (Max)
ID Card Capacity	10,000 (Max)
Record Capacity	Logs Capacity: 50,000 (MAX)
Display	5-inch IPS Full-View LCD Touch Screen Resolution: 1080 * 800
Communication	WiFi, LAN, TCP/IP Communication Protocol: HTTP (TLS encryption)
Standard Functions	Live face detection Door Alarm System Voice Broadcast Lan & WIFI Connectivity Cloud communication Cloud-based Tipsoi HRM software Real-Time Statistics Clock RTC Auto AGC, AEC & AWB balances Tipsoi Mobile App Enroll once and access anywhere
Interface	Relay, RS232, Wiegand output, Door Sensor, Exit Button, USB
Others	512 MB RAM, 4GB ROM CPU: Dual Core ARM Cortex-A7, 1GHz Function: Face, Card 2 (Infrared and RGB), 1 Megapixel Shutter Type: Electronic Rolling Shutter Anti-backlight RFID Supported RFID Card: Standard MIFARE Card, 13.56 MHz 99.99% Accuracy Live Face Detection: Yes (0.3 - 1.5m) (Configurable from device) FAR/ FRR for Face Recognition: 0.001/ 1(%) Face Recognition Mode: 1:1, 1:N Matching Speed: ≤ 0.5 sec, more than 30 face recognitions per minute WDR: 120dB Intelligent Update OS: Linux ON/OFF Control: Single built-in ON/OFF switch to control the power Battery Backup: 2.5-3 hours, with the replaceable battery pack.
Physical Specification	

Power Supply	DC 12V/2A Power Consumption: Max. 15W
Others	Temperature:-40℃ ~ +50℃ Working humidity: 10% ~ 90%
Manufacture Warranty	
Warranty	1 Year