

Marsriva MR-US3320K-H Energy Efficient 20kVA Online UPS

Sale Price: 216000.0



PRODUCT ID: 0015164

Main Feature	
Capacity	20kVA
Load Capacity	20kW
Input Voltage	3 x 400VAC (3Ph+N) / 230VAC (1Ph+N)
Output Voltage	3 x 360*/380*/400/415 VAC (3Ph+N)
Frequency (Battery Mode)	50Hz ± 0.1 Hz or 60Hz ± 0.1 Hz
Others	Output Harmonic Distortion (THDi): ≤2% THD (Linear Load) ; ≤5 % THD (Non-linear Load) Output Overload Capability: 100 – 110% for 60min, 111 – 125% for 10min, 126% – 150% 1min, > 150% immediately Input Harmonic Distortion (THDi): < 4% at full linear load
Input Features	
Frequency	46 – 54Hz @ 50Hz system; 56 – 64Hz @ 60Hz system
Power Factor	≥0.99 @ 100% Load
Voltage Range	110 – 300VAC ± 3 % @ 50% load; 176 – 276VAC ± 3 % @ 100% load
Output Features	
Type of Wave	Pure Sine wave
Transfer Time	AC Mode to Batt. Mode: 0ms Inverter to Bypass: 0ms
Manufacture Warranty	
Warranty	01-year warranty Under the following conditions, the warranty would not be provided: • UPS burning due to thunder, abnormal overload, insect entrance and others. • If ambient temperature should not be maintained at 20 to 26 degrees Celsius with proper dehumidification. (24/7) • If the product is placed in a dusty and damp place. • In the absence of Generator connectivity Without proper battery charge, the warranty will be void. • Battery swelling and overcharging due to the wrong system voltage setting of the UPS.