



ZKTeco SpeedFace-V5L Biometric Time Attendance and Access Control Terminal

Sale Price: 28500.0

PRODUCT ID: 0015186

Model	ZKTeco SpeedFace-V5L
Device Type	Hybrid Biometric Time Attendance & Access Control Terminal
Display	5-inch ISP Color LCD Touch Screen, 720 × 1280
Camera	2MP Binocular WDR Camera
Operating System	Linux
CPU	Quad Core A55 @ 1.2 GHz
RAM	512 MB; 1 GB optional for Palm
ROM / Storage	8 GB
Fingerprint Capacity	10,000 templates (1:N)
Face Capacity	10,000 templates (1:N)
Palm Capacity	3,000 templates (1:N), optional
Card Capacity	10,000 cards
User Capacity	10,000 users
Transaction Capacity	200,000 records
Authentication Methods	Face / Fingerprint / Palm / Card / Password
Fingerprint Sensor	Z-1D
Face Recognition Speed	< 0.35 sec
Fingerprint Verification Speed	< 0.5 sec
Palm Verification Speed	< 0.35 sec
Face Recognition Distance	30-170 cm
Palm Recognition Distance	15-40 cm
Face FAR	≤ 0.01%
Fingerprint FAR	≤ 0.0001%
Palm FAR	≤ 0.01%

Fingerprint FRR	≤ 0.01%
Palm FRR	≤ 0.17%
Card Support	125 kHz ID Card / 13.56 MHz IC Card, depending on module
QR Code	Dynamic QR via ZKBio CVAccess mobile app; optional
Communication	TCP/IP, Wiegand Input/Output, RS485
Wi-Fi	Optional, 2.4 GHz / 5 GHz
Access Control	Electric Lock, Door Sensor, Exit Button, Alarm, Auxiliary Input/Output
Access Control Interface	RS485 / ZKTeco RS485
Standard Functions	ADMS, DST, Photo Capture, Event Photo Capture, Access Levels, Groups, Holidays, Anti-Passback, Record Query, Tamper Alarm, Multiple Verification
User ID	Up to 14 digits
Virtual Keypad	16 Keys
Supplement Light	Yes
Video Intercom	Supported
ONVIF	Supported as optional function
Power Supply	DC 12V / 3A
Operating Temperature	-10°C to 45°C
Operating Humidity	10%–90% RH, non-condensing
Installation	Wall Mount
Dimensions	202.93 × 91.93 × 21.5 mm (L × W × H)
Net Weight	Approx. 0.6 kg
Gross Weight	Approx. 1.3 kg
Supported Software	ZKBio CVAccess, ZKBio Time, ZKBio Zlink
Certifications	ISO 14001, ISO 9001, CE, FCC