



## ZKTeco iClock260 Fingerprint Time Attendance and Access Control Terminal

Sale Price: 18900.0

PRODUCT ID: 0015201

|                                |                                                       |
|--------------------------------|-------------------------------------------------------|
| Brand                          | ZKTeco                                                |
| Model                          | iClock260                                             |
| Product Type                   | Fingerprint Time Attendance & Access Control Terminal |
| Fingerprint Sensor             | Optical Fingerprint Sensor                            |
| Fingerprint Capacity           | Up to 8,000 fingerprints                              |
| User Capacity                  | Up to 8,000 users                                     |
| Transaction Capacity           | Up to 200,000 transaction records                     |
| Face Recognition               | Not Supported                                         |
| Fingerprint Verification       | Supported                                             |
| Password Verification          | Supported                                             |
| RFID Card                      | Optional, depending on configuration                  |
| Card Types                     | ID / MIFARE / HID, depending on configuration         |
| Display                        | 3.5-inch TFT Color LCD                                |
| Display Resolution             | 320 × 240 pixels                                      |
| Keypad                         | Physical keypad                                       |
| User ID                        | 9-digit User ID                                       |
| Fingerprint Algorithm          | ZKFingerprint Algorithm                               |
| Fingerprint Verification Speed | ≤ 1 second                                            |
| False Acceptance Rate (FAR)    | ≤ 0.0001%                                             |
| False Rejection Rate (FRR)     | ≤ 1%                                                  |
| Communication                  | TCP/IP, RS232, RS485                                  |
| USB                            | USB Host / USB Client                                 |
| Wi-Fi                          | Optional, depending on version                        |
| Wiegand Input                  | Supported                                             |
| Wiegand Output                 | Supported                                             |
| Door Lock Control              | Supported                                             |
| Exit Button                    | Supported                                             |
| Door Sensor                    | Supported                                             |
| Alarm                          | Supported                                             |

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| Time Attendance          | Built-in                                                   |
| Work Code                | Supported                                                  |
| SMS Function             | Supported                                                  |
| Scheduled Bell           | Supported                                                  |
| DST                      | Supported                                                  |
| Automatic Status Switch  | Supported                                                  |
| T9 Input                 | Supported                                                  |
| Photo ID                 | Supported                                                  |
| Self-Service Query       | Supported                                                  |
| Web Server               | Optional                                                   |
| ADMS                     | Optional, depending on version                             |
| Software Support         | ZKTime.Net / BioTime, depending on system version          |
| Data Download            | USB / Network                                              |
| Data Upload              | USB / Network                                              |
| Power Supply             | DC 12V                                                     |
| Power Adapter            | Included, depending on package                             |
| Operating Temperature    | 0°C to 45°C                                                |
| Operating Humidity       | 20%–80%                                                    |
| Installation             | Wall Mount                                                 |
| Housing Material         | ABS / Plastic                                              |
| Dimensions               | Approx. 191.6 × 137.8 × 41 mm                              |
| Net Weight               | Approx. 0.7 kg                                             |
| Application              | Office, Factory, School, Shop, Warehouse, Organization     |
| Attendance Functions     | Check-in, Check-out, Overtime, Work Code, Shift Management |
| Access Functions         | Door Lock, Exit Button, Door Sensor, Alarm                 |
| Backup Method            | USB / Network                                              |
| Language Support         | Multiple languages, depending on firmware                  |
| Power Failure Protection | Internal data retention                                    |
| Mounting                 | Wall-mounted                                               |
| Typical Use              | Employee Attendance & Door Access Control                  |