

Apollo 2300HS 3KVA Standard Backup Online UPS

Sale Price: 43500.0



PRODUCT ID: 0015248

Main Feature	
Capacity	3.0 KVA
Load Capacity	<110% load Continuous 110-125% load 12 minutes 125-150% load 10 minutes >150% load: by pass
Input Voltage	Single Phase, 110Vac ~ 290Vac
Output Voltage	220Vac
Frequency (Battery Mode)	50/ 60Hz
Noise Level	<53dB - 65dB at 1 meter distance
Battery	DC Voltage: 96VDC Backup time: 15 - 30 Minutes depending on Load Recharge time: 5 ~ 8 Hours
Alarm	Audio Alarm: Keep 90 Seconds at a time interval of 4 Seconds Battery Low: Auto Shutdown upon complete discharge of battery and auto turn-on upon recovery of utility power Fault: Continuous Alarming
Input Features	
Frequency	50Hz (60Hz on Request) +/- 5%
Power Factor	>0.98% (Full Load)
Output Features	
Backup Time	15 - 30 Minutes depending on Load
Voltage Range	220Vac +/- 5%
Power Factor	0.8 ~ 1 (lagging)
Type of Wave	Pure Sinewave THD < 3%
Manufacture Warranty	

- UPS burning due to thunder, abnormal overload, insect entrance and others.
- If ambient temperature should not be maintained at 20 to 26 degrees Celsius with proper dehumidification. (24/7)
- If the product is placed in a dusty and damp place.
- In the absence of Generator connectivity Without proper battery charge, the warranty will be void.
- Battery swelling and overcharging due to the wrong system voltage setting of the UPS.