

GIGABYTE B760M D3HP DDR4 Micro ATX Motherboard

Sale Price: 16500.0



PRODUCT ID: 0007060

Basic Information

Supported CPU	LGA1700 socket: Support for the 14th, 13th, and 12th Generation Intel Core, Pentium Gold and Celeron Processors L3 cache varies with CPU
Chipset	Intel B760 Express Chipset
BIOS	1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor; 24.4cm x 24.4cm
Audio	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel

Expansion Slots

PCI	CPU: - 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 * The PCIEX16 slot can only support a graphics card or an NVMe SSD. Chipset: - 2 x PCI Express x1 slots, supporting PCIe 3.0 and running at x1
-----	--

Memory

Type	DDR4
Slots	4
Supported Memory	Support for DDR4 5333(O.C.)/ 5133(O.C.)/ 5000(O.C.)/ 4933(O.C.)/ 4800(O.C.)/ 4700(O.C.)/ 4600(O.C.)/ 4500(O.C.)/ 4400(O.C.)/ 4300(O.C.)/ 4266(O.C.)/ 4133(O.C.)/ 4000(O.C.)/ 3866(O.C.)/ 3800(O.C.)/ 3733(O.C.)/ 3666(O.C.)/ 3600(O.C.)/ 3466(O.C.)/ 3400(O.C.)/ 3333(O.C.)/ 3300(O.C.)/3200/3000/2933/2666/2400/2133 MT/s memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules

Information

Maximum Memory	Supporting up to 128 GB (32 GB single DIMM capacity) of system memory
----------------	---

Graphics

Graphics	Onboard Graphics Integrated Graphics Processor-Intel HD Graphics support: - 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz - 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version and HDCP 2.3. ** Support for native HDMI 2.1 TMDS compatible ports. - 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version and HDCP 2.3
----------	---

Connector & Ports

HDMI	1 x HDMI port
Display Port (s)	1 x DisplayPort
D-Sub (s)	1 x D-Sub port
USB (s)	Chipset: - 1 x USB Type-C port with USB 3.2 Gen 1 support, available through the internal USB header - 5 x USB 3.2 Gen 1 ports (3 ports on the back panel, 2 ports available through the internal USB header) - 2 x USB 2.0/1.1 ports on the back panel Chipset+USB 2.0 Hub: - 4 x USB 2.0/1.1 ports available through the internal USB headers
LAN Port (s)	Realtek GbE LAN chip (1 Gbps/100 Mbps/10 Mbps)
Supported Storage	CPU: - 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset: - 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB) - 4 x SATA 6Gb/s connectors
RAID	RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
Audio	3 x audio jacks

Information

Internal I/O Ports	Internal I/O Connectors 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 3 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C header, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x serial port header 1 x parallel port header 1 x S/PDIF Out header 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper Back Panel Connectors 2 x USB 2.0/1.1 ports 1 x PS/2 keyboard/mouse port 1 x D-Sub port 1 x DisplayPort 1 x HDMI port 3 x USB 3.2 Gen 1 ports 1 x RJ-45 port 3 x audio jacks
TPM (Trusted Platform Module)	1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 / GC-TPM2.0 SPI V2 module only)

Others

Special Features	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus
Bundled Software	Norton Internet Security (OEM version) LAN bandwidth management software

Warranty Information

Manufacturing Warranty	3 years Warranty
------------------------	------------------