

Dahua DHI-NVR1104HS-P-S3/H 04-Channel Compact 1U Lite POE NVR

Sale Price: 6000.0



PRODUCT ID: 0007806

Main Feature

Type	PoE NVR Switch
Port	HDD : 1 front USB 2.0 port, 1 rear USB 2.0 port USB : 1 HDMI : 1 VGA : 1 RCA Input : 1 RCA Output : 1 Alarm : None Network : 1 RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE power supply (10/100 Mbps)
Network Standard	Network Protocol : HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS, P2P Mobile Phone Access : iDMSS(iOS), gDMSS(Android) Access Standard : ONVIF(profile T/profile S/profile G),CGI,SDK Browser : Chrome, IE9 or above, Firefox
Access Method	Access Channel : 4 channels Network Bandwidth : 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Resolution : 8MP/5MP/4MP/3MP/1080P/720P/D1/CIF Decoding Capability : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output : 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P Multi-screen Display : 1/4 Third Party Camera Access : Onvif, RTSP

Advanced Functions

Multi-channel Playback : Up to 4 channels playback

Record Mode : Priority of record mode: Manual recording > alarm recording > motion detection recording > timed recording

Storage : Local HDD and network

Backup : USB device

Playback Function : 1. Play, pause, stop, fast forward, fast backward, rewind, play by frame 2. Full screen, backup (cut/file), partially enlarge, audio on/off

General Alarm : Motion detection, privacy masking, video loss, PIR alarm, IPC alarm

Anomaly Alarm : Front-end device going offline, storage error, full storage, IP conflict, MAC conflict, login lock, network security anomaly

Alarm Linkage : Video recording, snapshot, log, preset, tour

Compression

Video : Smart H.265+/H.265/Smart H.264+/H.264

Audio : PCM/G711A/G711U/G726/AAC

System

Main Processor : Industrial-grade embedded processor

Operating System : Embedded Linux

Operation Interface : Web/operating in local GUI

USB: 2 ports (1 Rear USB2.0, 1 Front USB2.0)

Internal HDD: 1 SATA III port, up to 10 TB for a single HDD. The maximum HDD capacity varies with environment temperature

Interoperability: ONVIF 2.4, SDK, CGI

Compression: Smart H.265+/H.265/Smart H.264+/H.264

Resolution: 8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.

Record Rate: 80Mbps

Bit Rate: 16Kbps ~ 20Mbps Per Channel

MAC Address Table

2K

Environment

Operating Conditions: -10°C to +55°C (+14°F to +131°F), 86–106kpa

Storage Conditions: 0°C to +40°C (+32°F to +104°F), 30–85% RH

Hardware

Features

Interface

1x HDMI, 1x VGA, 1x RJ-45 port (10/100/1000Mbps)

Power Supply

Single, DC48V/2A

Power Consumption: NVR: <5.8W (without HDD)

PoE: Max 25.5w for single port, 80w in total

Dimensions (L x W x H)

Compact 1U, 260 mm × 224.9 mm × 47.6 mm
 (10.2" × 8.9" × 1.9")

Weight

Net Weight: 0.8 kg (1.76 lb) (without HDD)

Gross Weight: 1.6 kg (3.53 lb) (without HDD)

Manufacture

Warranty

Warranty

1 Year