

Hotline-09614-502244


Sales-01979490143, Corporate- 01979999722 A Super Store Of Computer & Electronics Accessoriess MITCare- 01979490145, Warranty-01979490146 CCTV-01979490147, Web team- 01979999711


194, Banghabandhu Road, Shomobay New Market (2nd Floor) Shop No. 117-118,103-104, Chasara, Narayanganj-1400 www.munshiganjit.com.bd e-mail-info@munshiganjit.com.bd













194, Banghabandhu Road, Shomobay New Market (2nd Floor)

CAT-6 PROLINK NETWORKING CUTTING CABLE



Regular Price: 35.0 Sale Price: 30.0

PRODUCT ID: 01211

| Connection Class | |
|--------------------------------------|---|
| Standard | TIA/EIA-568A/568B & ISO 11801 |
| Shielding Connector | UTP |
| Connector Type | 23 AWG (4 pairs) |
| Category Connector | Cat6 |
| Physical Specs | |
| Dimensions | $390 \times 390 \times 235$ mm (L x W x H) Easy-pull boxes/Cable length of 305 M |
| Color | A White-Blue Stripe and a Blue B White-Orange Stripe and Orange C White-Green Stripe and Green D White-Brown Stripe and Brown |
| Cable Details | |
| Conductor | Material: CCA (Copper content: 35%) Conductor Diameter: 0.56±0.02mm Conductor Resistance MAX 18Ω/100m at 20°C Mutual Capacitance: MAX 5600pf/100M Resistance Unbalance: MAX 5% Resistance Unbalance: MAX 300pf/100M |
| Insulation | Insulation: High-Density Polyethylene Insulation Diameter: 0.93±0.02mm Insulation Nominal Wall Thickness: 0.2mm Insulation Resistance: MIN 150ΜΩ/ΚΜ |
| Twisting | 2 Insulated conductors twisted together |

Technical Detail



Hotline-09614-502244

Sales-01979490143, Corporate- 01979999722 CCTV-01979490147, Web team- 01979999711



A Super Store Of Computer & Electronics Accessoriess MITCare- 01979490145, Warranty-01979490146

194, Banghabandhu Road, Shomobay New Market (2nd Floor) Shop No. 117-118,103-104, Chasara, Narayanganj-1400 www.munshiganjit.com.bd e-mail-info@munshiganjit.com.bd









194, Banghabandhu Road, Shomobay New Market (2nd Floor)

| | | \sim 1 |
|-------|---------|----------|
| (onr | nection | (lass |
| COLL | | Class |

| Cable Designation | Cable Diameter: 5.6±0.15mm Printing: Each meter printed with a sequential length counter Jacket Nominal Wall Thickness: 0.7±0.01mm |
|-------------------|--|
| Outer Diameter | Cable Diameter: 5.6±0.15mm |
| Weight | 9.67kg/roll (Cable Only) 10.53kg (With Box) |
| Temperature ange | 75℃ |